

Safety Data Sheet

Section 1 - Product Information					
Product Name: Rinse Free				Supplier:	Intercon Chemical Company
Product Code Number: 8804		Information Phone: 314-771-6600		Address:	1170 Central Industrial Drive
Product use: Concentrated Rinse Aid		Emergency Contact: CHEMTREC 1-800-424-9300			St. Louis, MO 63110
Section 2 - Hazard Identification					
GHS classification: Eye Damage/Irritation - Category 2A; Skin Corrosion/Irritation - Category 2					
Section 2.1 - Label Elements					
Hazard Pictograms:		Precautionary Statements:			
		P264+P265: Wash hands thoroughly after handling. Do not touch eyes. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.			
		P337+P317: If eye irritation persists, get medical help. P302+P352: IF ON SKIN: Wash with plenty water. P362+P364: Take off contaminated clothes and wash before reusing. P332+P317: If skin irritation occurs: Get medical help. P321: Specific treatment see section 4 on SDS.			
Signal Word: Warning					
Hazard Statements: H315: Causes skin irritation H319: Causes serious eye irritation					
Section 3 - Composition					
Chemical Name	CAS #		Percent w/w		
Methyl Oxirane polymer	9003-11-6		1 - 5		
Sodium Xylene Sulfonate	1300-72-7		1 - 5		
Fatty Alcohol Alkoxylate	Trade Secret		1 - 5		
Butanedioic acid, sulfo-,1,4-dihexyl ester, sodium salt	3006-15-3		1 - 5		
Section 4 - First Aid Measures					
IF ON SKIN: Flush with flowing water for at least 15 minutes or until slippery feeling disappears. Get medical attention for any burns that may occur. Wash contaminated clothing before reuse.					
IF IN EYES: Flush with flowing water for 15 min. Remove contact lenses , if present and easy to do so. Continue Rinsing. Get medical help					
IF SWALLOWED: Rinse mouth. Do not induce vomiting. Get emergency medical help immediately.					
IF INHALED: Move to fresh air and keep at rest in a position comfortable for breathing.					
Section 5 - Fire and Explosion Hazard Data					
Flash Point:	Limits	Extinguishing Media:	Special Fire Fighting Procedures: Avoid exposure to fumes or vapors.		
NA	LEL: NA	Dry chemical, carbon dioxide if product involved.	Wear self-contained positive pressurized breathing apparatus		
	UEL: NA		MSHA/NIOSH Approved or equivalent to maintain TLV. UNUSUAL FIRE & EXPLOSION HAZARD: Product will not burn.		
Section 6 - Accidental Release Measures					
Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop leak if safe to do so. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). Scoop up material and place in a disposal container. Absorb spillage to prevent material damage. See section 13 for advice on waste disposal.					
Section 7 - Handling and Storage					
Do not get in eyes, on skin, or on clothing. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. Store locked up. Store upright in original closed container.					
Section 8 - Exposure Controls/PPE					
Ingredient:	OSHA PEL:	ACGIH TLV	PPE		General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practices. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.
Methyl Oxirane polymer	Not listed	Not listed	Respiratory:	not normally required	
Sodium Xylene Sulfonate	Not listed	Not listed	Eye:	safety glasses	
Fatty Alcohol Alkoxylate	Not listed	Not listed	Skin:	chemical resistant gloves	
Butanedioic acid, sulfo-,1,4-dihexyl ester, sodium salt	Not listed	Not listed	Ventilation:	Normal room ventilation	

Section 9 - Physical and Chemical Properties									
Appearance	Odor	Odor Threshold	pH	Melting Point	Boiling Point	Evaporation Rate	Flammability	Upper/Lower Flammability Limits	Vapor Pressure
Red Liquid	Pleasant	NE	< 4	NE	NE	NE	No	NA	17mm(Hg)
Vapor Density	Density (lbs/gal)	Specific Gravity	pH (1% dilution)	Solubility (H ₂ O)	Partition Coefficient	Auto Ignition Temp	Viscosity	Decomposition Temperature	
.62(air = 1)	8.5 lbs/gal	1.012	NE	complete	NE	NA	Thin	NE	
Section 10 - Stability and Reactivity									
Product is stable. Hazardous polymerization will not occur. It is incompatible with strong oxidizing agents. If burned normal combustion products such as Carbon Dioxide, Carbon Monoxide and Nitrous Oxides may occur.									
Section 11- Toxicological Information									
Ingredients	Acute toxicity(oral LD50) rat	Acute toxicity (derm. LD50) rabbit	Skin and Eye	Carcinogen	Mutagen	Reproduct. Toxicity	STOST -single Exposure	STOST Repeated exposure	
Methyl Oxirane polymer	>2,000mg/kg	>5000mg/kg	none	NE	NE	NE	NE	NE	NE
Sodium Xylene Sulfonate	16,200mg/kg	2,000mg/kg	irritant	NE	NE	NE	NE	NE	NE
Fatty Alcohol Alkoxylate	>2,000mg/kg	NE	irritant	NE	NE	NE	NE	NE	NE
Butanedioic acid, sulfo-,1,4-dihexyl ester, sodium salt	>1750mg/kg	>5mL/kg	irritant	NE	NE	NE	NE	NE	NE
Section 12 - Ecological Information					Section 13 - Disposal Considerations				
Not Established.					The products covered by this SDS, in their original form, are considered nonhazardous waste according to RCRA(40 CFR 261). Dispose of in accordance with applicable Federal, State and Local regulations.				
Section 14 - Transport Information									
UN number	Basic Description (DOT)					Class	Packing Group	LTD QTY	
	Not Regulated								
UN number	Basic Description (IATA)					Class	Packing Group	LTD QTY	
	Not Regulated								
UN number	Basic Description (IMDG)					Class	Packing Group	LTD QTY	
	Not Regulated								
Section 15 - Regulatory Information									
SARA Title 3: Alcohols C8-10, ethers. For more information consult sections 302, 304, or 313 of Title III of the Superfund amendments and Reauthorization Act of 1986.									
CERCLA: Phosphoric Acid (RQ = 5,000 lbs). For more information consult 40 CFR parts 302, 355, 370, 372, and 40 CFR part 68.									
	Warning: This product can expose you to chemicals including Aniline (CAS# 62-53-3), Ethylene glycol (CAS# 107-21-1), Ethylene oxide (CAS# 75-21-8), and Propylene oxide (CAS# 75-56-9) which are known to the State of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov								
Section 16 - Other Information									
		HMIS: Health - 1		Flam. - 0	R - 0	PPE- A			
Date Prepared: 13 Aug 2025		Prepared by: Director of Technical Service, Research and Development							
The information provided in this Safety Data Sheet is correct to the best of our knowledge and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with materials or in any process, unless specified in the text.									
Legend for Abbreviations: GHS - Globally Harmonized System; CAS - Chemical Abstracts Service; NA - Not Applicable; MSHA - Mine Safety and HealthAdministration; NIOSH - National Institute for Occupational Safety and Health; TLV - threshold limit value; PPE - personal protection equipment; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; ACGIH - American Conference of Governmental and Industrial Hygienists;NE - Not Established; STOT - Specific Target Organ Toxicity; HMIS - Hazard Materials Identification System; NOEC - No Observed Effect Concentration; CERCLA -Comprehensive Environmental Response, Compensation, and Liability Act; RQ - DOT Reportable Quantity; DOT - Department of Transportation (49 CFR parts 100 to 185); IATA - International Air Transport Association; IMDG - International Code for the maritime transport of Dangerous Goods; WHMIS - Workplace Hazardous Materials Information System (Canada).									