

# alumasafe detergent

Non-Chlorinated Liquid Warewash Detergent

## **Product Properties**

COLOR: Clear, Colorless
ODOR: Characteristic

pH: 13.0 FOAMING: None to Flash

SOLUBILITY IN WATER: Complete

RINSABILITY: Free Rinsing

HARD WATER TOLERANCE: Excellent

## **Description**

This product is a non-chlorinated liquid warewash detergent designed for all temperature warewashing and for use in automatic hood cleaning systems. It is fortified with a special water conditioning package for tackling tough jobs. It is very economical, yet strong enough for most applications.

### Features...Benefits

Highly Concentrated ...... Economical

Aluminum Safe ..... Protects Facility Investment

Versatile ..... Ease of Use

Hard Water Tolerant ..... Labor Saving

Low Foam System ..... Improved Efficiency

#### **Directions**

READ AND UNDERSTAND LABEL AND SAFETY DATA SHEET (SDS) BEFORE USE. **USE DILUTION:** Concentration varies due to environmental conditions. Your sanitation specialist will properly adjust product concentrations to meet your needs. DO NOT MIX WITH ANYTHING BUT WATER. FOR LOW TEMPERATURE **WAREWASHING:** 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. 4. In rinse cycle, use a recommended rinse additive. 5. Sanitize using an approved chlorinated sanitizer at 50 ppm. Test using chlorine test papers or a liquid chlorine test kit. 6. Allow dishes to air dry. FOR HIGH TEMPERATURE WAREWASHING: 1. Pre-flush and/or scrape dishes before washing. 2. Rack dishes properly. Place dishes in machine. 3. Wash using this product. Concentration will vary due to environmental conditions. Maintain wash temperature at 150°-160°F. 4. In rinse cycle, use a recommended rinse additive. Be sure rinse injector is working properly. Maintain rinse temperature at 180°-190°F. 5. Allow dishes to air dry. FOR AUTOMATIC HOOD CLEANING: Formulated to split grease and oils, without the use of emulsifiers and without harm to stainless steel or aluminum. Product should be fed directly from shipping container for convenient use.

NOTE: Proper care and protective equipment are required for manual cleaning - see the SDS.

1100 Central Industrial Dr. St. Louis, Missouri, 63110

toll free: 800 325 9218 main: 314 771 6600 fax: 314 771 6608

www.interconchemical.com



230427-0709 © INTERCON 2023 REFER TO PRODUCT LABEL AND SDS FOR ADDITIONAL INFORMATION