



chloro foam

**CHLORINATED
ALKALINE
FOAMING
DEGREASER**

Product Properties

COLOR: Clear Amber

ODOR: Chlorine

pH: 13.0

SPECIFIC GRAVITY: 1.15

FOAMING: High

Description

This highly concentrated, chlorinated, foaming cleaner is designed to quickly penetrate and remove a wide variety of soils in the food and beverage processing environment. It effectively lifts animal fats, greases and other food residues while completely stripping protein films from equipment, cutting blocks, walls, floors, etc. Compatible with most foam generating equipment and spray washers or can be used manually.

Features...Benefits

Emulsifies fats and grease

Deep penetration and lifting action removes all types of soil

May be applied by use of foam generating equipment

Cleans rapidly - rinses freely - non flammable

Chlorinated for fast protein film removal

Directions

MANUAL APPLICATION: Dilute 1 part of this product with 15 to 20 parts of hot water. Apply by mop, spray or other suitable means such as sponge or cloth. Rinse with hot water.

SPRAY APPLICATION: For most cleaning operations the proportioning device in the sprayer should be set to dilute the concentrate to 20 or more parts of water. Apply hot foam liberally to all washable surfaces including floors, walls, tables, etc. Allow foam to cling to surface for at least 5 minutes. Rinse using hot water. Let surfaces drain dry. Do not wipe dry. Tilt movable surfaces to aid water run-off.

Safety Information

KEEP OUT OF REACH OF CHILDREN

DANGER: Contains alkaline builders and sodium hypochlorite. Causes eye and skin burns. In case of contact with eyes, flush with water for 15 minutes and call a physician. In case of contact with skin, flush thoroughly with water and call a physician if irritation persists. Do not take internally. In case of ingestion, drink plenty of water or milk and call a physician.

1100 Central Industrial Dr.
St. Louis, Missouri, 63110

toll free: 800 325 9218
main: 314 771 6600
fax: 314 771 6608

www.interconchemical.com

**INTERCON™**

Letter of guarantee available upon request.

180226-0716
© INTERCON 2018

**REFER TO PRODUCT LABEL AND SDS
FOR ADDITIONAL INFORMATION**