


ultra soak



LIQUID PRESOAK

Product Properties

COLOR: Clear Pink
ODOR: Pleasant
VISCOSITY: 10 cps
pH: 14
SPECIFIC GRAVITY: 1.04
FOAMING: Good
DETERGENCY: Excellent
HARDWATER TOLERANCE: Excellent

Description

Specially formulated for presoaking and detarnishing of flatware, this product performs equally well in hard or soft water. Contains ingredients which aid in the reduction of water spotting on flatware, as well as loosening cooked-on soils.

Features...Benefits

ConcentratedEconomical
Reduces Water SpottingImproved Results
Reduces Dishmachine "Rejects"Labor Saving
DetarnishesLabor Saving
Reduces Dishmachine Detergent UseEconomical

Directions

STAINLESS FLATWARE - Add 1/2 to 1 ounce per gallon of warm water in a sink or other vessel. Soak flatware from 1 to 5 minutes depending on soil, then rack and pass through dishwasher. They will come out clean, shiny and spot-free.

SILVER PRESOAK - Add 1/2 to 14 ounces per gallon of warm water in a vessel lined with aluminum foil. As silverware is brought back to washing area, place it in this vessel. Allow it to soak a few minutes, then rack and pass through dishwasher. Silverware will be cleaner and shine like never before.

FAST DETARNISHING - Add 1 to 2 ounces per gallon of hot water in a vessel lined with aluminum foil. Place silverware in a basket and soak in this solution 1 to 3 minutes. Withdraw silverware, rinse in hot water and dry to a shine. (NOTE: Do not allow silver to soak too long as this will cause redeposition of aluminates on your utensils.)

Safety Information

KEEP OUT OF REACH OF CHILDREN

WARNING: Causes irritation or burns to eyes and skin. Avoid contact with eyes and skin. In case of contact, flush immediately with plenty of water. For eyes, seek medical attention. If swallowed, drink plenty of water and seek medical attention.

1100 Central Industrial Dr.
St. Louis, Missouri, 63110

toll free: 800 325 9218
main: 314 771 6600
fax: 314 771 6608

www.interconchemical.com



Letter of guarantee available upon request.

151209-0773
© INTERCON 2015

**REFER TO PRODUCT LABEL AND SDS
FOR ADDITIONAL INFORMATION**