


Big Boy



BUILT LAUNDRY

Product Properties

COLOR: Violet
ODOR: Detergent
pH: 13.1
SPECIFIC GRAVITY: 1.13
HARD WATER TOLERANCE: High Tolerance

THIS PRODUCT IS NOT AVAILABLE FOR USE OR SALE IN THE STATE OF NEW YORK.

Description

This product is an excellent answer to tough institutional laundry challenges. This concentrated formula contains surfactants and soluble alkalis to completely remove a wide variety of soils. It does not redeposit soils, and contains water softeners to prevent graying of hard water scale build-up. It also protects machines with corrosion inhibitors. It is formulated for multi-component automatic dispensing systems and may be used with chlorine bleach. Use this product on your toughest, most troublesome laundry problems to experience its outstanding cleaning performance.

Features...Benefits

Concentrated Economical
Hard Water Tolerant Improved Performance
Non-Foaming Improved Results

Directions

For automatic injection systems program dispenser to add correct amount of detergent with suds cycle flush.

100 POUND CAPACITY.....6 to 8 oz.

50 POUND CAPACITY.....3 to 5 oz.

35 POUND CAPACITY.....1 to 2 oz.

For household type machines add 2 to 3 ounces with wash water fill. After all items of liquid system are set, including bleach, run a test load of badly soiled and stained linens to observe the remarkable cleaning. Check for alkali residue and adjust softener/sour as needed. See your sales representative for specific laundry handling instructions.

Safety Information

This is a caustic detergent containing potassium hydroxide. Wear proper PPE when handling this product. Flush skin or eyes with water for 15 minutes if contact occurs. Avoid breathing vapor or spray, and remove to fresh air if inhaled. If ingested, give water or milk, but do not induce vomiting. Call a physician or poison control center immediately.

1100 Central Industrial Dr.
St. Louis, Missouri, 63110

toll free: 800 325 9218
main: 314 771 6600
fax: 314 771 6608

www.interconchemical.com



230104-7883
© INTERCON 2023

REFER TO PRODUCT LABEL AND SDS
FOR ADDITIONAL INFORMATION