



Description

High Alkaline Detergent is a concentrated, high performance, low foaming alkaline detergent and cleaner used for removing a wide range of organic soils and residues from stainless steel cages, glassware, and mechanical equipment. **High Alkaline Detergent** is designed for use inside washer-disinfectors, cart washers, cage washers, glassware washers, and in Clean-In-Place (CIP) applications.

Features

- High performance removal of most organic soils including proteins, synthetic organics, oils, waxes, etc.
- Low foaming, free rinsing, and excellent hard water tolerance
- Ideal for cart, rack, and cage washers, sinks, and spray applications

Directions for Use

High Alkaline Detergent should be dosed at 0.10-3.0 oz./gal. of water (0.8-24 mL/L), at temperatures ranging from room temperature to 180°F (82°C). Ideal dose and temperature will depend on the soil type and load, the substrates being cleaned, and the overall water quality being used. Always follow machine manufacturers' instructions for use.

Safety

Be sure to don appropriate Personal Protection Equipment (PPE).

This product is intended for industrial and institutional use only. Not intended for consumer use.

High Alkaline Detergent is compatible with stainless steel, glassware, and most plastics.

Consult the Safety Data Sheet (SDS) for more detailed information pertaining to safety, handling, storage, and waste disposal methods.

DO NOT ADD BLEACH or any other chemical to **High Alkaline Detergent**. Combining chemicals outside of the directions for use could result in loss of efficacy or adverse chemical reactions.

The product is freeze/thaw stable. If frozen, thaw to room temperature and shake or stir.

Once the container is empty, rinse and dispose of properly. Do not reuse this container. Any detergent waste should be disposed of according to Federal, State, and/or local regulations.



High Alkaline Detergent

High Alkaline,
Low Foam Detergent

Properties

Color: Colorless liquid

Odor: Mild chemical odor

Product pH: >12.5

Store below 120°F (49°C)

Use up to 35 months from date of manufacture

Package Sizes Available

5 Gallons (TH)	FICCB-CP-005T-8431
15 Gallons	FICCB-CP-0015-8431
55 Gallons	FICCB-CP-0055-8431



Refer to Product Label and SDS for Additional Information.

314-771-6600 • 800-325-9218 • interconchemical.com

1100 Central Industrial Dr, St. Louis, MO 63110

2025 Intercon Chemical Company.

