

interplex 18

THERMOPLASTIC FLOOR FINISH

Product Properties

COLOR (LIQUID): Opaque White
COLOR (DRIED): Clear Colorless
ODOR: Mild
pH: 8-9
FLASH POINT: None
SPECIFIC GRAVITY: 1.02
NON VOLATILE SOLIDS: 18.0%
LEVELING: Excellent
COVERAGE: AVG. 2000 sq.ft./gal.

Description

This state-of-the-art thermoplastic finish combines the ultimate in toughness with a crystal clear "wet look" gloss in a labor saving, high solids formula. Excellent leveling that dries to a tough, yet flexible, film. Easily maintained to an extended service life with compatible cleaners and buffing compounds. The low odor level of this product makes it more pleasant to use than traditional type finishes.

Features...Benefits

Extremely Tough Film Improved Performance
Provides Extended Service Life Labor Saving
Excellent Leveling Easy to Use
Dries Bright Labor Saving
Multi-Speed Buffable Easy to Use

Directions

Apply to cleaned or stripped floor in a uniform coat using a clean mop or applicator. Allow to dry and recoat. Apply a minimum of 3 coats to establish a sound base coating. Maintain with cleaners as recommended. Periodic restoring is optional. Traffic aisles should be thoroughly scrubbed clean before recoating as part of a regular maintenance program. Follow the Floor Care Procedures as listed in the INTERCON FLOOR CARE MANUAL.

Safety Information

KEEP OUT OF REACH OF CHILDREN

CAUTION

DO NOT TAKE INTERNALLY. Avoid contact with skin, eyes and clothing. IF ON SKIN, wash with soap and water immediately. Seek medical attention if irritation persists. IF IN EYES, flush with flowing water for 15 minutes and seek medical attention. IF INGESTED, drink milk or water to dilute material. DO NOT induce vomiting. Call a physician or poison control center immediately.

REFER TO PRODUCT LABEL AND SDS
FOR ADDITIONAL INFORMATION

161115-0314
© INTERCON 2016

1100 Central Industrial Dr.
St. Louis, Missouri, 63110

toll free: 800 325 9218
main: 314 771 6600
fax: 314 771 6608

www.interconchemical.com

**INTERCON™**